Switchboards for level and pressure monitoring HRH-ECH and TPS-ECH

Simply automate the operation of the pump wherever it is necessary to drain conductive liquids from the tank when the maximum level is reached.


- Automation of pump start-up in tanks with conductive liquid
- The set has MCB only for relay and contactor only. It is necessary to install a suitable circuit breaker for the pump
- The switchgear is UV-resistant, IP65.
- Choice of monitoring one or two levels
- Probes are not included can be supplied.
- Supply voltage: 230V (50-60Hz)
- One or two level monitoring


A set of switches for automatic operation of 1 and 3-phase pumps. In several versions. The contactor version does not load the relay with higher motor currents, the pump switching is done by a motor contactor with contacts rated for AC3 loads. Everything is prepared and wired in a plastic ECH switchboard with IP65 protection and transparent door.

Cable glands are included in the package.



Principle of connection






HRH-ECH-MS-CEC

Equipped level control switchboards HRH-ECH-MS-CEC with level switch, motor starter and contactor for 3-phase pumps in wall-mounted plastic ECH-8

- Motor starter with protection against overload and short-circuit protection, depending on motor power
- Circuit breaker short-circuit resistance 10kA
- Level relay HRH-5
- Contactor CEC 09 or CEC16.10-230V-50/60Hz

Order code	Name	Contactor	Motor current (A)	Motor power (kW)
004483610	TPS-ECH-MS2-CEC		1,6-2,5	0,75
004483611	TPS-ECH-MS4-CEC	CEC09	2,5-4	1,1-1,5
004483612	TPS-ECH-MS6-CEC		4-6,3	2,2-2,5
004483613	TPS-ECH-MS10-CEC	CEC016	6,3-10	3-4








Can also be manufactured for other pump motor outputs on request


HRH-ECH-CEC

Equipped level control switchboards with level switch and contactor for 3-phase pumps in wall-mounted plastic ECH-8

- Circuit breaker short-circuit resistance 10kA
- Level relay HRH-5
- Contactor CEC 09 or CEC16.10-230V-50/60Hz

Order code	Name	Contactor	Motor current (A)	Motor power (kW)
004483608	HRH-ECH-CEC09	CEC09	6,3	2,5
004483609	HRH-ECH-CEC16	CEC016	16	5,5







Can also be manufactured for other pump motor outputs on request


HRH-ECH-MS1F-CEC

Equipped level control switchboards with level switch, motor starter and contactor for 1-phase pumps in wall-mounted plastic ECH-8

- Circuit breaker short-circuit resistance 10kA
- Level relay HRH-5
- Contactor CEC 09 or CEC16.10-230V-50/60Hz
- Motor starter with protection against overload and short-circuit protection, depending on motor power

Order code	Name	Contactor	Motor	Motor
			current (A)	power (kW)
004483604	HRH-ECH-MS41F-CEC	CEC09	2,5-4	0,37-0,55
004483605	HRH-ECH-MS61F-CEC	CECOS	4-6,3	0,55-0,75
004483606	HRH-ECH-MS101F-CEC	CEC016	6,3-10	1,1-1,5
004483607	HRH-ECH-MS161F-CEC		10-16	2,2









TPS-ECH-MS-CEC

Equipped switchgear for float and digital pressure switches, with level switch, motor starter and contactor for 3-phase pumps in wall-mounted plastic ECH-8

- Circuit breaker short-circuit resistance 10kA
- Contactor CEC 09 or CEC16.10-230V-50/60Hz
- Motor starter with protection against overload and short-circuit protection, depending on motor power

Order code	Name	Contactor	Motor	Motor
			current (A)	power (kW)
004483610	TPS-ECH-MS2-CEC		1,6-2,5	0,75
004483611	TPS-ECH-MS4-CEC	CEC09	2,5-4	1,1-1,5
004483612	TPS-ECH-MS6-CEC		4-6,3	2,2-2,5
004483613	TPS-ECH-MS10-CEC	CEC016	6,3-10	3-4







Sensors for level control relay

Order code	Name	Description
002471205	SHR-1-M	Brass sensor, without cable, Smax = 2,5mm², operating temperature (-25 to 60°C)
002471709	SHR-1-N	Stainless steel sensor, without cable, Smax = 2,5mm², operating temperature (-25 to 60°C)
002471203	SHR-2	Stainless steel sensor, without cable, Smax = 2,5mm², operating temperature (1 to 80°C), IP68
002471230	SHR-3	Stainless steel sensor, with 3m cable PVSC 2x0,75mm², operating temperature < 95°C, IP67





